


DESCRIPTION					
Total Thickness	EN ISO 24346	mm	9.5		
Weight	EN ISO 23997	g/m <sup>2</sup>	9880		
Size	EN ISO 24342	mm	229 x 1235	298 x 620	229 x 1815
Number of planks /tiles and sqm per box	-	-	6 / 1.70 m <sup>2</sup>	6 / 1.11 m <sup>2</sup>	5 / 2.08 m <sup>2</sup>
CLASSIFICATION					
Norm/Product Specification	-	-	EN 16511		
European Classification	EN ISO 10874	class	32		
Fire Rating	EN 13 501-1	class	Bfl-s1		
Static Electrical Propensity	EN 1815	kV	< 2		
Slip Resistance Wet	DIN 51130	class	R10		
PERFORMANCES					
Impact sound insulation	EN ISO 717-2	dB	16		
Dimensional Stability	EN ISO 23999	%	≤ 0.15		
Residual Indentation	EN ISO 24343-1	mm	≤ 0.10		
Castor chair test	ISO 4918	-	OK		
Thermal Conductivity	EN ISO 10456	W/(m.K)	0.25		
Colour Fastness	EN 20 105 - B02	degree	≥ 6		
Surface Treatment	-	-	PUR+ MATT		
Chemical Products Resistance	EN ISO 26987		OK		
ENVIRONMENT / INDOOR AIR QUALITY					
TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 100		
CE MARKING					
	EN 14041		